

PROJECTION OPTICAL SYSTEM, EXPOSURE APPARATUS,
AND DEVICE MANUFACTURING METHOD

FIELD OF THE INVENTION AND RELATED ART

5 This invention relates to a projection
optical system for projecting a pattern of a
reticle in a reduced scale, by use of EUV (extreme
ultraviolet) light. More particularly, the
invention concerns a projection optical system for
10 performing reduction projection by use of a
plurality of mirrors, of a number of about six,
for example.

A projection optical system for
performing reduction projection by use of mirrors
15 of a number of about six, is disclosed in, for
example, U.S. Patent No. 5,686,728, No. 6,172,825
(Japanese Laid-Open Patent Application No. 2000-
100694), or No. 6,353,470 (Japanese Laid-Open
Patent Application No. 2000-235144).

20 However, in the projection optical
systems disclosed in these documents, one or more
mirrors (in many cases, the first or second mirror
in the order from the reticle side) have a
curvature radius having a large absolute value,
25 such as 1600 mm or more. In fact, in the examples
among these projection optical systems in which
the second mirror in the order from the reticle

side is very the mirror that is placed closest to the reticle, the curvature radius of one or more mirrors has a very large absolute value, such as an enormous value of 2000 mm or more.

5 If the curvature radius of a mirror is large, the size of a measuring machine such as an interferometer system required for measuring the curvature radius or shape of the reflection surface (aspherical surface) of the mirror becomes
10 too large. For example, in order to measure the surface shape of a concave mirror having a curvature radius of 2000 mm by use of an interferometer, the concave mirror must be placed at a position away from the measurement beam
15 convergence position by 2000 mm or more.

 In such interferometer, since the distance between the reflection surface of the mirror (subject of measurement) and a reference surface is more than 2000 mm, the measurement is
20 easily influenced by fluctuation of the refractivity of the ambience such as air. Further, although it depends on the type of interferometer used, the visibility of interference fringe decreases due to the relation of coherence length.
25 Hence, the precision for the measurement of surface shape or curvature radius of the mirror is quite low.

As described, in conventional projection optical systems, there is a problem that the measurement precision for the surface shape of one or more mirrors is low and, thus, the mirror surface-shape precision is low. For this reason, the imaging performance of a projection optical system can not be improved easily.

SUMMARY OF THE INVENTION

It is accordingly an object of the present invention to provide a projection optical system by which the above-described problem can be solved or reduced.

In accordance with an aspect of the present invention, there is provided a projection optical system for performing reduction projection of a pattern of a reticle, comprising: a first mirror having a concave surface shape; a second mirror having a concave surface shape; a third mirror having a convex surface shape; a fourth mirror having a concave surface shape; a fifth mirror having a convex surface shape; and a sixth mirror having a concave surface shape, wherein said first to sixth mirrors being disposed in the named order along an optical path from the reticle side, and wherein each of the six mirrors has a curvature radius having an absolute value not

greater than 1500 mm.

In one preferred form of this aspect of the present invention, the projection optical system further comprises an aperture stop disposed adjacent said second mirror.

Among the six mirrors, said second mirror may have a curvature radius having a largest absolute value.

Among the six mirrors, said first mirror may have a curvature radius having a largest absolute value.

Among the six mirrors, said second mirror may be disposed closest to the reticle.

Among the six mirrors, the or each mirror having an effective diameter greater than 400 mm may have a curvature radius having an absolute value not greater than 1000 mm.

Each of the six mirrors may have a reflection surface of aspherical shape.

Five mirrors of the six mirrors may have a curvature radius having an absolute value not greater than 1300 mm.

Five mirrors of the six mirrors may have a curvature radius having an absolute value not greater than 1250 mm.

Four mirrors of the six mirrors may have a curvature radius having an absolute value

not greater than 700 mm.

Four mirrors of the six mirrors may have a curvature radius having an absolute value not greater than 630 mm.

5 The first mirror may have a conic coefficient k_1 that satisfies a relation $50 < k_1 < 150$.

 The first mirror may have a conic coefficient k_1 that satisfies a relation $80 < k_1 < 130$.

 The fifth mirror may have a conic
10 coefficient k_5 that satisfies a relation $5 < k_5 < 20$.

 The fifth mirror may have a conic coefficient k_5 that satisfies a relation $7.5 < k_5 < 12$.

 The projection optical system may perform reduction projection of the reticle
15 pattern by use of extreme ultraviolet light.

 The projection optical system may be constituted only by said first, second, third, fourth, fifth and sixth mirrors.

 In accordance with another aspect of
20 the present invention, there is provided an exposure apparatus, comprising: a projection optical system as recited above, for performing reduction projection of a pattern of a reticle; and an illumination optical system for
25 illuminating the reticle with extreme ultraviolet light.

 In one preferred form of this aspect of

the present invention, the projection optical system is constituted only by the first, second, third, fourth, fifth and sixth mirrors, wherein the extreme ultraviolet light from the reticle is
5 directed by these six mirrors to a substrate to be exposed.

In accordance with a further aspect of the present invention, there is provided a device manufacturing method, comprising the steps of:
10 exposing a substrate with a device pattern by use of an exposure apparatus as recited above; and developing the exposed substrate.

These and other objects, features and advantages of the present invention will become
15 more apparent upon a consideration of the following description of the preferred embodiments of the present invention taken in conjunction with the accompanying drawings.

20 BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic view of an optical system according to a first embodiment of the present invention.

Figure 2 is a schematic view of an
25 optical system according to a second embodiment of the present invention.

Figure 3 is a schematic view of an

optical system according to a third embodiment of the present invention.

Figure 4 is a schematic view of an exposure apparatus according to an embodiment of the present invention.

Figure 5 is a flow chart for explaining semiconductor device manufacturing processes.

Figure 6 is a flow chart for explaining details of a wafer process, in the procedure of the flow chart of Figure 5.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will now be described with reference to the attached drawings.

A projection optical system according to an embodiment of the present invention has a design wavelength 13.5 nm and a reduction magnification, and it has a basic structure of six mirrors including, in the order of reflection of light from an object plane side (reticle side), a concave mirror (mirror M1), a concave mirror (mirror M2), a convex mirror (mirror M3), a concave mirror (mirror M4), a convex mirror (mirror M5), and a concave mirror (mirror M6). Each of these six mirrors has a curvature radius having an absolute value not greater than 1500 mm.

Hence, in accordance with the present embodiment, there is provided a projection optical system for performing reduction projection of a pattern of a reticle by use of extreme ultraviolet (EUV) light having a wavelength not less than 10 nm and not greater than 20 nm, wherein the projection optical system includes six mirrors, that is, a first mirror M1 of concave surface shape, a second mirror M2 of concave surface shape, a third mirror M3 of convex surface shape, a fourth mirror M4 of concave surface shape, a fifth mirror M5 of convex surface shape, and a sixth mirror M6 of concave surface shape, disposed in the named order to sequentially reflect the light, and wherein each of the six mirrors has a curvature radius having an absolute value not greater than 1500 mm. As a result, a measuring machine (interferometer) to be used to measure the curvature radius of the mirrors or the surface shape of the reflection surface of the mirrors can be made compact. Additionally, the measurement precision for the surface shape of the six mirrors becomes very good, and thus the precision of the mirror surface shape can be improved significantly. Therefore, the imaging performance of the projection optical system can be improved notably. If there is a mirror having a curvature radius of

an absolute value greater than 1500 mm, the measurement precision for the surface shape of such mirror would be degraded and the surface shape precision of that mirror would be

5 deteriorated thereby. Therefore, it would be very difficult to improve the imaging performance of the projection optical system.

Preferably, five mirrors of the six mirrors may have a curvature radius having an
10 absolute value not greater than 1300 mm (more preferably, not greater than 1250 mm).

Alternatively, four mirrors of the six mirrors may preferably have a curvature radius having an absolute value not greater than 700 mm (more
15 preferably, not greater than 630 mm). In the projection optical system according to the present embodiment, four mirrors M1 - M4 are arranged to form an intermediate image which is in turn re-imaged by two mirrors M5 and M6 upon the image
20 plane (wafer surface).

In the projection optical system according to this embodiment, among the six mirrors, the or each mirror having an effective diameter greater than 400 mm has a curvature
25 radius having an absolute value not greater than 1000 mm. In Examples 1 - 3 to be described below, the mirror M4 is the mirror greater than 400 mm.

However, any other mirror or mirrors may have a size greater than 400 mm.

At least one mirror of the six mirrors may have a reflection surface of aspherical surface shape. From the standpoint of aberration correction, many mirrors as much as possible may have a reflection surface of aspherical surface shape. It may be most desirable to provide all the six mirrors with a reflection surface of aspherical surface shape.

The projection optical system of this embodiment basically comprises a coaxial optical system being axially symmetrical with respect to a single optical axis, and aberration is corrected in terms of a ring-like (field of) image plane about the optical axis. However, for aberration correction or adjustment, at least one of the six mirrors may be disposed with small eccentricity.

In the projection optical system of this embodiment, the mirror M2 is the mirror that is disposed closest to the object plane. This is effective to make the diameter of the mirror M4 relatively small. As regards the positional relationship among the mirrors M1, M2 and M4, in respect to the mirror vertex position, the mirror M4 is disposed between the mirrors M1 and M2. This arrangement makes the diameter of the mirror

M4 relatively small on one hand, and it makes the aspherical amount of the reflection surface of the mirrors M3 and M4 relatively small on the other hand.

5 Further, in relation to correction of the field curvature, the sum of the refractive powers of the reflection surfaces of the mirrors M1 - M6 is made close to zero. More specifically, if the curvature radii of the mirrors M1 - M6,
10 close to the optical axis, are denoted by r_1 , r_2 , r_3 , r_4 , r_5 and r_6 , respectively, the value $1/r_1 - 1/r_2 + 1/r_3 - 1/r_4 + 1/r_5 - 1/r_6$ is made equal to zero or close to zero.

 In the projection optical system of
15 this embodiment, the above-described conditions are satisfied and, in addition to it, other aberrations are corrected. Also, for enhanced practicality in regard to the size of the optical system, $r_1 - r_6$ are set in the following ranges:
20 $r_1 = -1400 \pm 100$, $r_2 = 1200 \pm 100$, $r_3 = 450 \pm 150$, $r_4 = 600 \pm 200$,
 $r_5 = 350 \pm 100$, $r_6 = 500 \pm 100$.

 The reflection surfaces of the mirrors M1 - M6 are provided with a multilayered film for reflecting the extreme ultraviolet (EUV) light.
25 Where the design wavelength is 13.5 nm as in the examples to be described later, a multilayered reflection surface, comprising Mo and Si, is

provided.

An aperture stop is defined at or adjacent the mirror M2 position. The mirror M2 itself may function as an aperture stop, or
5 alternatively, a separate aperture stop member or variable aperture stop member may be provided adjacent the mirror M2 to restrict or variably set the numerical aperture (NA).

Assuming that a reflection type reticle
10 (mask) is mounted on the object plane, the projection optical system of this embodiment is designed as an optical system which is non-telecentric on the object side and is telecentric on the image side. Since the principal ray at the
15 image plane side of the projection optical system emerges in parallel to the optical axis of the projection optical system, even if a photosensitive member (wafer) mounted on the image plane shifts in the optical axis direction, the
20 change in magnification is small.

In the projection optical system of this embodiment, at least one mirror has an aspherical reflection surface having an aspherical surface shape Z that can be expressed by the
25 following equation:

$$Z = ch^2/[1+\text{SQRT}(1-(1+k)c^2h^2)] + Ah^4 + Bh^6 + Ch^8 + Dh^{10} + Eh^{12} + Fh^{14} + Gh^{16} + Hh^{18} + Jh^{20} + \dots$$

where Z is the coordinates with respect to the optical axis direction, c is the curvature (inverse of curvature radius r), h is the height from the optical axis, k is the conic coefficient, and $A, B, C, D, E, F, G, H, J$ and so on are aspherical coefficients of fourth-order, sixth-order, eighth-order, tenth-order, twelfth-order, fourteenth-order, sixteenth-order, eighteenth-order, twentieth-order, and so on. Here, the conic coefficient k means that the above-described aspherical surface is based on a hyperbola if $k < 0$, a parabola if $k = 0$, an ellipsoid (a plane obtainable by rotating an ellipse about its major axis) if $0 < k < 1$, a spherical surface if $k = 1$, and an ellipsoid (a plane obtainable by rotating an ellipse about its minor axis) if $k > 1$.

For better aberration correction, in the projection optical system of this embodiment, the conic coefficient k_1 of the mirror M_1 satisfies a relation $50 < k_1 < 150$ and, also, the conic coefficient k_5 of the mirror M_5 satisfies a relation $5 < k_5 < 20$. The mirrors M_1 and M_5 have aspherical surfaces based on an oblate spheroid. More preferably, k_1 may be set to satisfy a relation $80 < k_1 < 130$ and k_5 may be set to satisfy a relation $7.5 < k_5 < 12$.

It is another feature of the projection

optical system of this embodiment that an intermediate image is imaged at the midpoint (between M4 and M5). This makes the NA large and enables better aberration correction.

5 Specific examples of a projection optical system according to this embodiment of the present invention will be described below.

[Examples]

10 Figures 1 - 3 illustrate optical paths in section of Example 1, Example 2 and Example 3, respectively, of a projection optical system according to this embodiment of the present invention. In these drawings, the same reference
15 numerals are assigned to corresponding elements.

 In Figures 1 - 3, denoted at MS is a reflection type reticle which is mounted at an object plane position. Denoted at W is a workpiece (wafer) to be exposed, and it is mounted
20 at an image plane position. Denoted at M1 is a first mirror (concave mirror), and denoted at M2 is a second mirror (concave mirror). Denoted at M3 is a third mirror (convex mirror), and denoted at M4 is a fourth mirror (concave mirror).
25 Denoted at M5 is a fifth mirror (convex mirror), and denoted at M6 is a sixth mirror (concave mirror). Denoted at AX is an optical axis.

As the reticle MS is illuminated with EUV light of a wavelength of about 13.5 nm, from an illumination optical system (not shown), in the projection optical system the EUV light from the
5 reticle MS is reflected sequentially in the order of first mirror M1 (concave mirror), second mirror M2 (concave mirror), third mirror M3 (convex mirror), fourth mirror M4 (concave mirror), fifth mirror M5 (convex mirror) and sixth mirror M6
10 (concave mirror), whereby a reduced image of a device (circuit) pattern of the reticle is formed on the wafer W which is placed at the image plane position.

In Example 1, the projection optical
15 system has a design wavelength $\lambda = 13.5$ nm, NA = 0.20, a reduction magnification of 1/4, an arcuate object plane (region) with an object height of 125 - 135 mm, an arcuate image plane (region) with a width 2.5 mm, at an image height of 31.25 - 33.75
20 mm.

In Example 2, the projection optical system has a design wavelength $\lambda = 13.5$ nm, NA = 0.25, a reduction magnification of 1/4, an arcuate object plane (region) with an object height of 128
25 - 136 mm, an arcuate image plane (region) with a width 2 mm, at an image height of 32 - 34 mm.

In Example 3, the projection optical

system has a design wavelength $\lambda = 13.5$ nm, NA = 0.28, a reduction magnification of 1/4, an arcuate object plane (region) with an object height of 132 - 136 mm, an arcuate image plane (region) with a width 1 mm, at an image height of 33 - 34 mm.

Tables 1 - 3 below show optical data (curvature radius, surface spacing, aspherical coefficient and so on) of the projection optical system according to Example 1, Example 2, and Example 3, respectively.

[Table 1]

Example 1:

Mirror	Curvature	Surface	Conical
Number	Radius	Spacing	Coefficient k
MS(reticle)	INFINITY	630.179916	
M1	-1417.99439	-261.467870	108.912559
M2	1239.25392	418.624113	-0.359058
M3	362.77769	-201.547857	0.353432
M4	474.63367	768.506284	0.044131
M5	355.39768	-433.958427	8.409102
M6	516.18902	479.663841	0.087959
W(Wafer)	INFINITY		

ASPHERICAL COEFFICIENT

M1 :

A :0.683291E-08

B :0.920316E-13

C	:0.569325E-17	D	:0.336108E-22
E	:0.298242E-25	F	:-.192742E-29
G	:0.113727E-33	H	:0.000000E+00
J	:0.000000E+00		

5 M2 :

A	:-.527660E-09	B	:-.146866E-13
C	:-.120097E-17	D	:0.602378E-22
E	:0.202254E-24	F	:-.112453E-27
G	:0.173326E-31	H	:0.000000E+00

10 J :0.000000E+00

M3 :

A	:-.389938E-08	B	:-.193071E-13
C	:0.895942E-18	D	:-.339434E-22
E	:-.285140E-26	F	:0.286164E-30
G	:-.777425E-35	H	:0.000000E+00
J	:0.000000E+00		

15

M4 :

A	:-.199437E-09	B	:0.176911E-14
C	:-.449370E-19	D	:0.472723E-24
E	:-.363016E-29	F	:0.258718E-34
G	:-.134850E-39	H	:0.000000E+00
J	:0.000000E+00		

20

M5 :

A	:-.222962E-07	B	:-.230654E-12
C	:-.570785E-16	D	:-.805423E-20
E	:0.121605E-23	F	:0.168015E-28
G	:-.382728E-31	H	:0.000000E+00

25

J :0.000000E+00

M6 :

A :-.293665E-10 B :-.606092E-16
 C :-.512438E-21 D :0.445912E-25
 E :-.249950E-29 F :0.714531E-34
 G :-.817258E-39 H :0.000000E+00
 J :0.000000E+00

10 [Table 2]

Example 2:

Mirror	Curvature	Surface	Conical
Number	Radius	Spacing	Coefficient k
MS(reticle)	INFINITY	643.602181	
15 M1	-1447.35247	-261.656816	101.944633
M2	1215.95679	405.854887	0.642114
M3	455.18256	-300.124352	1.824126
M4	608.71774	865.720173	0.041252
M5	348.99083	-432.357964	10.791670
20 M6	515.45674	476.357972	0.089726
W(wafer)	INFINITY		

ASPHERICAL COEFFICIENT

M1 :

25 A :0.609140E-08 B :0.699773E-13
 C :0.418382E-17 D :0.285464E-22
 E :0.195221E-25 F :-.223251E-29

G : 0.243045E-33 H : -.131967E-37
J : 0.353573E-42

M2 :

5 A : -.520732E-09 B : -.158879E-13
 C : 0.199750E-18 D : -.272652E-20
 E : 0.391908E-23 F : -.323621E-26
 G : 0.154875E-29 H : -.400536E-33
 J : 0.433411E-37

M3 :

10 A : -.361756E-08 B : -.100951E-13
 C : -.188622E-17 D : 0.137421E-21
 E : -.435870E-27 F : -.807975E-30
 G : 0.416642E-34 H : 0.745306E-39
 J : -.744094E-43

15 M4 :

 A : -.708692E-11 B : -.587545E-15
 C : 0.415278E-20 D : 0.233903E-25
 E : -.428472E-30 F : -.288671E-35
 G : 0.446209E-40 H : 0.204972E-45
20 J : -.274443E-50

M5 :

 A : -.290931E-07 B : -.100431E-11
 C : -.126109E-15 D : -.580717E-20
 E : -.249237E-24 F : 0.990307E-28
25 G : -.215115E-30 H : 0.737415E-34
 J : -.863420E-38

M6 :

A :-.267143E-10 B :-.448332E-16
 C :-.774133E-21 D :0.126998E-24
 E :-.131738E-28 F :0.876886E-33
 5 G :-.358801E-37 H :0.820550E-42
 J :-.801112E-47

[Table 3]

10 Example 3:

Mirror	Curvature	Surface	Conical
Number	Radius	Spacing	Coefficient k
MS (reticle)	INFINITY	644.850299	
M1	-1423.28830	-264.078564	100.234610
15 M2	1218.20499	405.736540	0.789243
M3	446.68480	-291.988234	1.752538
M4	598.88100	861.479959	0.029391
M5	349.11713	-432.237976	10.738888
M6	515.55439	476.237976	0.090117
20 W(wafer)	INFINITY		

ASPHERICAL COEFFICIENT

M1 :

A :0.627121E-08 B :0.755850E-13
 25 C :0.428200E-17 D :0.622819E-22
 E :0.161861E-25 F :-.179291E-29
 G :0.213411E-33 H :-.119178E-37

J :0.337956E-42

M2 :

A :-.519569E-09 B :-.152324E-13
C :0.827001E-18 D :-.447137E-20
E :0.643682E-23 F :-.530372E-26
G :0.253310E-29 H :-.653936E-33
J :0.706349E-37

M3 :

A :-.376490E-08 B :-.152265E-13
C :-.157948E-17 D :0.153611E-21
E :-.436540E-26 F :-.856327E-30
G :0.895218E-34 H :-.290000E-38
J :0.162538E-43

M4 :

A :-.358812E-11 B :-.590866E-15
C :0.420854E-20 D :0.267696E-25
E :-.475021E-30 F :-.372201E-35
G :0.729697E-40 H :-.717295E-46
J :-.180920E-50

M5 :

A :-.292071E-07 B :-.992125E-12
C :-.118939E-15 D :-.753027E-20
E :-.578063E-24 F :0.886658E-27
G :-.595140E-30 H :0.157698E-33
J :-.159492E-37

M6 :

A :-.274252E-10 B :-.467321E-16

C	:-.124139E-20	D	:0.193090E-24
E	:-.193399E-28	F	:0.124502E-32
G	:-.495959E-37	H	:0.111156E-41
J	:-.106975E-46		

5

The aberration of the projection optical systems in the preceding examples of this embodiment is as follows:

Example 1: wavefront aberration = 0.031 λ rms;

10 distortion (range) = 8 nm

Example 2: wavefront aberration = 0.010 λ rms;

distortion (range) = 1.2 nm

Example 3: wavefront aberration = 0.027 λ rms;

distortion (range) = 0.9 nm

15

Thus, in these examples, a diffraction limited optical system in regard to the wavelength 13.5 nm was accomplished.

20

In the projection optical systems according to Examples 1 - 3, the image plane (region) has an arcuate shape (ring-like shape) and, therefore, where a projection optical system of any one these examples is incorporated into a projection exposure apparatus, the exposure method to be used is such that a reticle and a wafer are scanningly moved in the widthwise direction of this arcuate shape at a speed ratio the same as the reduction magnification of the projection

25

optical system by which the exposure regions (to be exposed) on the wafer (normally, plural regions are disposed in array) are exposed with the whole reticle pattern.

5 It should be noted here that the present embodiment is not limited to the examples described above. The structure may be changed within the scope of the present invention to improve the performance.

10 Next, an exposure apparatus into which a projection optical system according to the present invention is incorporated, will be described. The exposure apparatus of the present invention may use extreme ultraviolet (EUV) light
15 having a wavelength of 13.4 nm, for example, as illumination light for the exposure process.

Further, as described hereinbefore, the image plane of a projection optical system 100 has an arcuate shape (ring-like shape), and the exposure
20 method used is such that the whole surface of the reticle is exposed (transferred) by scanningly moving the reticle and the wafer at a speed ratio corresponding to the reduction magnification.

Referring to Figure 4, the exposure
25 apparatus has an extreme ultraviolet (EUV) light source 210, an illumination optical system 220, a reflection type reticle 230, an alignment optical

system 240, a projection optical system 100, a reticle stage 250, a wafer stage 260, and a wafer 270.

Since the EUV light has a very low transmissivity with respect to an atmospheric air, preferably the light path along which the EUV light passes may be maintained in a vacuum ambience. To this end, the path from the illumination optical system 220 to the wafer stage 260 is accommodated in a vacuum container 280.

The EUV light source 210 of this embodiment may comprise a laser plasma light source, for example. In the laser plasma light source 210, a large-intensity pulse laser light is projected onto a target member 213, supplied by a target supplying device 211 and placed inside the vacuum container 280, from a pulse laser 211 and through a condenser lens 214, whereby high temperature plasma 215 is produced. From this plasma, EUV light of a wavelength of about 13.4 nm is emitted and it is used. The target member 213 may comprise a metal thin film, an inactive gas or liquid drops. It is supplied into the vacuum container 280 by means of the target supplying device which may comprise a gas jet, for example.

The illumination optical system 220 illuminates the reticle 230 by propagating the EUV

light. In Figure 3, the illumination optical system 220 includes first, second and third mirrors 221, 222 and 223, an optical integrator 224, and an aperture 225. The first mirror 221
5 functions to collect EUV light having been emitted isotropically from the plasma 215. The optical integrator 224 serves to uniformly illuminate the reticle 230, with a predetermined numerical aperture. Here, the EUV light is relayed to the
10 reticle 230 by means of the second and third mirrors 222 and 223. The aperture 225 is disposed at a position in the illumination optical system which position is optically conjugate with the reticle 230, and it functions to restrict the
15 illumination region upon the reticle 230, to be illuminated, into an arcuate shape.

The reticle stage 250 and the wafer stage 260 are provided with a scanning mechanism by which they are scanningly moved in synchronism
20 with each other, at a speed ratio proportional to the reduction magnification. Here, within the plane of the reticle 230 or wafer 270, the scan direction is referred to as X direction, and a direction perpendicular thereto is referred to as
25 Y direction. The direction perpendicular to the plane of the reticle 230 or wafer 270 is referred to as Z direction.

The reticle 230 is formed with a desired pattern, and it is held by a reticle chuck (not shown) mounted on the reticle stage 250. The reticle stage 250 is provided with a driving
5 mechanism for moving it in X direction. Also, it has a fine-motion mechanism with respect to each of X, Y and Z directions as well as rotational directions about these axes, such that the reticle 230 can be positioned precisely. The position and
10 attitude of the reticle stage 250 are measured by laser interferometers, and the position and attitude are controlled on the basis of the result of measurement. In this embodiment, the reticle 230 is a reflection type reticle. However, either
15 a transmission type reticle or a reflection type reticle may be used.

The wafer 270 is held on the wafer stage 260 by means of a wafer chuck, not shown. Like the reticle stage 250, the wafer stage 260 is
20 provided with a driving mechanism for moving it in X direction. Also, it has a fine-motion mechanism with respect to each of X, Y and Z directions as well as rotational directions about these axes, such that the wafer 270 can be positioned
25 precisely. The position and attitude of the wafer stage 260 are measured by laser interferometers, and the position and attitude are controlled on

the basis of the result of measurement.

The alignment detecting optical system 240 functions to measure the positional relationship between the position of the reticle 230 and the optical axis of the projection optical system 100, as well as the positional relationship between the position of the wafer 270 and the optical axis of the projection optical system 100. On the basis of the measurement, the positions and angles of the reticle stage 250 and the wafer stage 260 are set so that a projected image of the reticle 230 is registered with a predetermined position on the wafer 270. Further, a focus detecting optical system (not shown) is provided to measure the focus position of the wafer 270 surface with respect to Z direction. By controlling the position and angle of the wafer stage 260 on the basis of the measurement, the wafer surface can be held at the imaging position of the projection optical system 100, constantly during the exposure process.

When a single scan exposure on the wafer 270 is completed, the wafer stage 260 is moved stepwise in X and Y directions, toward a next scan exposure start position, and then the reticle stage 250 and the wafer stage 260 are scanningly moved again in X direction, at a speed

ratio proportional to the reduction magnification of the projection optical system.

In this manner, the operation that the reticle 230 and the wafer 270 are synchronously scanningly moved while a reduced projected image of the reticle 230 is being imaged on the wafer 270 is repeated (step-and-scan), and the pattern of the reticle 230 is transferred to the whole surface of the wafer 270.

Next, referring to Figures 5 and 6, an embodiment of a device manufacturing method which uses an exposure apparatus described above, will be explained.

Figure 5 is a flow chart for explaining the procedure of manufacturing various microdevices such as semiconductor chips (e.g., ICs or LSIs), liquid crystal panels, or CCDs, for example. Step 1 is a design process for designing a circuit of a semiconductor device. Step 2 is a process for making a mask on the basis of the circuit pattern design. Step 3 is a process for preparing a wafer by using a material such as silicon. Step 4 is a wafer process which is called a pre-process wherein, by using the thus prepared mask and wafer, a circuit is formed on the wafer in practice, in accordance with lithography. Step 5 subsequent to this is an

assembling step which is called a post-process wherein the wafer having been processed at step 4 is formed into semiconductor chips. This step includes an assembling (dicing and bonding) process and a packaging (chip sealing) process. Step 6 is an inspection step wherein an operation check, a durability check and so on, for the semiconductor devices produced by step 5, are carried out. With these processes, semiconductor devices are produced, and they are shipped (step 7).

Figure 6 is a flow chart for explaining details of the wafer process, at step 4 in Figure 5. Step 11 is an oxidation process for oxidizing the surface of a wafer. Step 12 is a CVD process for forming an insulating film on the wafer surface. Step 13 is an electrode forming process for forming electrodes upon the wafer by vapor deposition. Step 14 is an ion implanting process for implanting ions to the wafer. Step 15 is a resist process for applying a resist (photosensitive material) to the wafer. Step 16 is an exposure process for printing, by exposure, the circuit pattern of the mask on the wafer through the exposure apparatus described above. Step 17 is a developing process for developing the exposed wafer. Step 18 is an etching process for

removing portions other than the developed resist image. Step 19 is a resist separation process for separating the resist material remaining on the wafer after being subjected to the etching process.

5 By repeating these processes, circuit patterns are superposedly formed on the wafer.

With these processes, high density microdevices can be manufactured.

10 While the present invention has been described with reference to some preferred embodiments, the invention is not limited to these embodiments. Many modifications and changes are possible within the scope of the invention.

15 In accordance with the embodiments of the present invention described hereinbefore, a projection optical system with which the imaging performance can be improved significantly is accomplished.

20 While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or changes as may come within the purposes of the improvements or the scope of the
25 following claims.